

LED HIGH BAY LIGHT DOME SERIES



LED HIGH BAY LIGHT DOME SERIES

picture				
model no.	60W-3030	100W-3030	150W-3030	200W-3030
rated power	60W	100W	150W	200W
input voltage	AC85-265V	AC85-265V	AC85-265V	AC85-265V
LED & driver	Philips 3030 + Meanwell driver			
luminous flux	Philips 3030 chip :115lm/w			
CCT options	Philips3030: 3000K ±200K, 4000K ±200K, 5000K ±200K, 5700K ±200K, 6500K ±200K			
beam angle	90°/120°	90°/120°	90°/120°	90°/120°
material	Aluminum 1070+PC	Aluminum 1070+PC	Aluminum 1070+PC	Aluminum 1070+PC
size	D230 x 200MM			
lifespan (Hrs)	50 000	50 000	50 000	50 000
power Eff	≥0.95	≥0.95	≥0.95	≥0.95
CRI	≥80Ra	≥80Ra	≥80Ra	≥80Ra
IP grade	IP54	IP54	IP54	IP54
warranty	3 years	3 years	3 years	3 years
working environment	Temp:-20° -50° Humidity:5-95%R.H.	Temp:-20° -50° Humidity:5-95%R.H.	Temp:-20° -50° Humidity:5-95%R.H.	Temp:-20° -50° Humidity:5-95%R.H.
net weight	1.8kg	2.9kg	4.6kg	5kg
gross weight	2.3kg	3.4kg	5.1kg	5.5kg
certification	CE, Rohs	CE, Rohs	CE, Rohs	CE, Rohs

